

Specifications*

Prowler Automatic 4WD RTV

Power Plant:	660 cc 4-stroke, Liquid Cooled, Electric Start with Auxiliary Auto-Decompression Recoil Pull
Power Train:	Fully Automatic Transmission with Hi/Lo Range, Reverse and Park Function; Push Button 2WD/4WD/4WD Lock
Operation:	Standard Automotive Driver Controls with Sealed Rack and Pinion Steering
Suspension:	Front - Independent Double Wishbone, Adjustable Preload, 8" Travel Rear - Independent Double Wishbone, Adjustable Preload, 9" Travel
Braking:	Front - Dual Hydraulic Discs Rear - Shaft Mounted Hydraulic Disc with 4 Piston Opposed Caliber
Instrumentation:	Digital Multi-Function Display with LCD Speedometer/Odometer, Dual Trip Meters, Hour Meter and Clock, Electronic Fuel Gage and Drive Train Position Indicators
Fuel Capacity:	4.5 gal. plus two optional Saddle Tanks
Payload:	800 lb plus
Towing Capacity:	1212 lbs
Dry Weight:	795 lbs, bias: 52% Front, 48% Rear
Length:	91.5" Overall
Width:	52" (Track Width: 45" Front, 43" Rear)
Height:	64" (41" w/o detachable roll cage, quick disconnect steering wheel and seat; 35" if suspension collapsed)
Wheel Base:	57"
Ground Clearance:	12" (13.5" @ Approach & Departure)

*These specifications are subject to change without notice

ALL TERRAIN VEHICLE CORP., is a subsidiary of PHOENIX INTERNATIONAL SYSTEMS, Inc.,
an ISO-9000 CERTIFIED MANUFACTURER

